

Optimized sleep mode operation

BACKGROUND OF THE INVENTION

5

1. Field of the Invention

The invention relates to operations in TDD (time division duplex) mode in third generation cellular telecommunication systems. Especially, the invention is related to such a method as specified in the preamble of the independent method claim.

10

2. Description of Related Art

15

With reference to Figure 1, a typical third generation mobile telephone system structure will be shortly described. Only those functional blocks are shown which have certain importance to the description of the present invention; it is obvious to a person skilled in the art that a common mobile telephone system also comprises other functions and structures, which need not be discussed in greater detail here. The main parts of the mobile telephone system are: a CN or a core network 101, a UTRAN or UMTS terrestrial radio access network 102 and a UE or user equipment 103. The user equipment is often called a mobile terminal or a mobile communication means. The interface between the CN and the UTRAN is called the Iu interface, and the interface between the UTRAN and the UE is called the Uu interface.

25

The UTRAN is composed of RNSs or radio network subsystems 104. The interface between two RNSs is called the Iur interface. The RNS comprises a RNC or radio network controller 105 and one or more node Bs 106. The interface between an RNC and a node B is called the Iub interface. Each node B gives rise to at least one coverage area, i.e. cell, which is designated in Figure 1 by 107.

30

Presently the development of third generation cellular systems is headed towards the use of a plurality of communication techniques and transmission modes over the air interface. For example, according to current plans, conventional GSM mobile phones can be used also with third generation cellular systems via GSM-capable radio access networks (UTRAN). Many other transmission modes will also be supported. The present application concerns the UTRA (UMTS Terrestrial Radio Access) TDD (time division duplex) mode.

35

In the UTRA TDD system all physical channels have the structure of radio frames and timeslots. The frame has a duration of 10 ms and is subdivided into 15 time slots (TS). A time slot corresponds to 2560 chips. The time slots separate different user signals in the time domain, and several bursts can be sent in the same slot separated by different spreading codes. Each of the time slots can be allocated to either the uplink or the downlink. The allocation can be nearly symmetric or even highly asymmetric, if needed. At least one time slot has to be allocated for the downlink and at least one time slot has to be allocated for the uplink. The flexibility in the allocation of time slots in uplink and downlink directions allows the TDD mode to be adapted to highly differing environments.

The data symbols of a channel is sent in bursts. One burst is transmitted in a time slot. Figure 2 shows the structure of a burst. A burst comprises a first data part, a midamble, a second data part and a guard period. Two types of bursts are defined in UTRA TDD, which have different lengths for the data parts and the midamble. Figure 2 shows the lengths of a type 1 burst, data parts being 976 chips long and the midamble 512 chips long. The midamble of a type 2 burst is 256 chips long, and the data parts 1104 chips long. The guard period in both types of bursts is 96 chips long. The midamble of a burst carries no payload data. The midamble functions as a training sequence for use by a receiver in signal acquisition and tracking.

The UTRA TDD mode is described in more detail in various 3GPP (3rd Generation Partnership Project) specifications, such as the TS 25.221 V3.0.0 specification describing physical channels and mapping of transport channels onto physical channels.

* In UTRA TDD the paging mechanism uses two channels, namely the PICH (Paging Indicator CHannel) and the PCH (Paging CHannel). Paging messages are carried in the PCH, and the PICH carries only indications, if paging messages relating to mobile terminals in a given paging group are to be expected. The paging channel is transmitted over a paging area (PA) which may comprise one or more cells. The number of mobile terminals within the paging area can be large, whereby the traffic volume of the paging channel can also be large. This means that if a mobile terminal were to receive paging messages only with the help of the PCH, the mobile terminal would have to listen to paging messages of PCH, which would consume an excessive amount of time for the terminal. This would cause excessive power consumption especially during sleep mode, in which the power consumption of

mobile terminals should be as low as possible. The paging indicators carried in PICH indicate to each paging group of mobile terminals, if a paging message is to be expected on the PCH to some terminal of the paging group. Receiving of a paging indicator requires only receiving of a single burst and decoding the data bits of the burst to obtain the paging indicator values. The paging indicators are sent at predetermined intervals, so that terminals can stay in sleep mode between the paging indicator bursts. If a paging indicator indicates that a paging message is to be expected for the paging group of a particular mobile terminal, that mobile terminal begins to listen to PCH for a certain period to find out, if any paging messages are intended to that mobile terminal. Terminals in a paging area are divided into 60 paging groups, which allows the number of mobile terminals to stay rather low. The low number of terminals in a paging group results in a low number of paging messages intended for terminals in the group, whereby the terminals need to listen to PCH only for short periods of time. This results in a low power consumption in the sleep mode.

However, a mobile terminal also needs to monitor the quality of the radio link to the current cell of the mobile terminal. If the quality of the radio link degrades for example due to moving of the terminal out of the coverage area of the cell, the mobile terminal needs to perform a handover to another cell. For this purpose, a mobile terminal needs to receive a burst in the PCCPCH (Primary Common Control Physical Channel) and measure the reception level of the midamble of a burst carrying PCCPCH information. If the reception level is too low, the terminal needs to start searching and listening to neighboring cells to find a cell, whose transmissions the terminal can receive at a sufficient level.

Although the use of PICH already optimizes the sleep mode operations rather well, reception of PICH bursts and monitoring the strength of the PCCPCH channel still requires a terminal to leave the sleep state quite often. "The prior art does not teach any way to further reduce the necessity to receive and consequently the power consumption of the mobile terminal."

SUMMARY OF THE INVENTION

An object of the invention is to realize a method, which allows better optimization of sleep mode operation for TDD terminals. A further object of the invention is to realize a method, which allows a further reduction in the time required for reception of paging indicators and for measuring radio link quality. A still further object of the

invention is to realize a TDD mode mobile terminal with a better optimized sleep mode operation than mobile terminals according to prior art. A further object of the invention is to provide a system in a radio access network, which allows the TDD mode mobile terminals under control of the radio access network to further reduce the time required for reception of paging indicators and for measuring radio link quality.

The objects are reached by adjusting the transmission level of the midamble of a PICH burst to a level, which has a predefined relation to the transmission level of a PCCPCH burst. This allows a TDD mode terminal to receive a single PICH burst, and determine the paging indicators and the reception level of the PCCPCH channel.

The method according to the invention is characterized by that, which is specified in the characterizing part of the independent method claim. The mobile terminal according to the invention is characterized by that, which is specified in the characterizing part of the independent claim directed to a mobile terminal. The system according to the invention is characterized by that, which is specified in the characterizing part of the independent claim directed to a system. The dependent claims describe further advantageous embodiments of the invention.

According to the invention, the power level of midamble of the burst sent in the slot of the PICH channel has a predefined relation to the power level of the bursts sent at the primary CCPCH channel. This allows the mobile communication means to receive only one burst for obtaining both desired pieces of information by decoding the PICH bits to find out if a paging message is to be received, and measuring the reception level of the midamble of the PICH burst for determining the quality of the radio connection.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments of the invention will be described in detail below, by way of example only, with reference to the accompanying drawings, of which

Figure 1 illustrates an UMTS system according to prior art,

Figure 2 illustrates burst structure in UTRA TDD mode according to prior art,

Figure 3 illustrates a method according to an advantageous embodiment of the invention,

5 Figure 4 illustrates a method according to a further advantageous embodiment of the invention,

Figure 5 illustrates a mobile terminal according to an advantageous embodiment of the invention,

10 Figure 6 illustrates a system according to an advantageous embodiment of the invention.

15 A description of Figures 1 and 2 was given earlier in connection with the description of the state of the art. Same reference numerals are used for similar entities in the figures.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20 According to a first aspect of the invention, a method for transmitting paging indicators in a cellular telecommunication system employing time division duplex mode is provided. In the method, information is carried in bursts over the air interface, and paging indicators are carried in data part of certain bursts having at least a data part and a training sequence part. In an advantageous embodiment of the invention the transmission level of at least the training sequence part of a burst

25 carrying paging indicators has a predefined relation to the transmission level of the training sequence part of a burst belonging to a channel which is used in measurements of radio link quality. In a further advantageous embodiment said channel is the primary common control physical channel (PCCPCH).

30 In an advantageous embodiment of the invention, said predefined relation is that the transmission level of at least the training sequence part of a burst carrying paging indicators is essentially the same as the transmission level of the training sequence part of a burst belonging to said channel. In other embodiments of the invention the transmission levels can also be different, i.e. the relation may be for example such

35 that the transmission level of the training sequence i.e. the midamble of the PICH burst has a certain predetermined offset to the transmission level of the PCCPCH burst.

In an advantageous embodiment of the invention, the midamble of the PICH slot has a predefined power offset compared to the midamble of PCCPCH. The PICH slot can be sent with a lower level than the PCCPCH although the PICH needs to be heard in the whole cell, since in some cases the PICH symbols may be repeated,
 5 which increases the probability of correct reception.

Figure 3 illustrates a method for transmitting paging indicators in a cellular telecommunication system employing time division duplex mode according to an advantageous embodiment of the invention. In step 210, the transmission level of a
 10 PICH burst is set to a level having a predefined relation to the transmission level of the training sequence part of a burst belonging to a channel which is used in measurements of radio link quality. In step 220, the PICH burst is transmitted at such a level.

15 In an advantageous embodiment of the invention, the determination of the transmission level of the midamble of PICH bursts is performed during network planning phase, when the transmission levels for base stations are determined. The transmission level of the PICH bursts can in such an embodiment be determined to be essentially the same as the transmission level of PCCPCH bursts.

20 According to a second aspect of the invention, a method in a mobile terminal of a cellular telecommunication network is provided for measuring quality of a radio link between the mobile terminal and a base station of the network. Figure 4 shows an example of such a method according to an advantageous embodiment of the invention. The method is applicable with mobile terminals arranged to employ time
 25 division duplex mode and to receive bursts carrying information from the base station, the bursts having at least a data part and a training sequence part, and which mobile terminals are arranged to receive paging indicators carried in certain bursts. In an advantageous embodiment of the invention the method comprises steps, in
 30 which

- a burst carrying paging indicators is received 410,
- the reception level of the training sequence part of said burst is measured 420, and
- a result value indicating the quality of the radio link is determined 430 on the basis of said measurement of the reception level of the training sequence part of said
 35 burst.

According to a third aspect of the invention, a mobile terminal of a cellular telecommunication network is provided. The mobile terminal is arranged to employ

time division duplex mode and to receive bursts carrying information from the base station, the bursts having at least a data part and a training sequence part. The mobile terminal is also arranged to receive paging indicators carried in certain bursts. According to an advantageous embodiment of the invention, the mobile terminal comprises

- means for receiving a paging indicator burst,
- means for measuring the reception level of the training sequence part of said paging indicator burst, and
- means for determining a result value indicating the quality of the radio link on the basis of the output of said means for measuring.

Fig. 5 shows a block diagram of a mobile terminal, in this example a digital mobile communication means according to an advantageous embodiment of the invention. The mobile communication means comprises a microphone 301, keyboard 307, display 306, earpiece 314, antenna duplexer or switch 308, antenna 309 and a control unit 305, which all are typical components of conventional mobile communication means. Further, the mobile communication means contains typical transmission and receiver blocks 304, 311. Transmission block 304 comprises functionality necessary for speech coding, encryption, and modulation, and the necessary RF circuitry for amplification of the signal for transmission. Receiver block 311 comprises the necessary amplifier circuits and functionality necessary for demodulating and decryption of the signal, and removing speech coding. The signal produced by the microphone 301 is amplified in the amplifier stage 302 and converted to digital form in the A/D converter 303, whereafter the signal is taken to the transmitter block 304. The transmitter block encodes the digital signal and produces the modulated and amplified RF-signal, whereafter the RF signal is taken to the antenna 309 via the duplexer or switch 308. The receiver block 311 demodulates the received signal and removes the encryption and channel coding. The resulting speech signal is converted to analog form in the D/A converter 312, the output signal of which is amplified in the amplifier stage 313, whereafter the amplified signal is taken to the earpiece 314. The control unit 305 controls the functions of the mobile communication means, reads the commands given by the user via the keypad 307 and displays messages to the user via the display 307. In this exemplary embodiment of the invention, the mobile communication means comprises means 308, 309, 311 for receiving a paging indicator burst, means 330 for measuring the reception level of the training sequence part of said paging indicator burst, and means 340 for determining a result value indicating the quality of the radio link on the basis of the output of said means for measuring.

According to a fourth aspect of the invention, a system in a radio access network of a cellular telecommunication system is provided. The system is applicable in cellular telecommunication systems employing time division duplex mode, in which mode
 5 information is carried in bursts over the air interface, and in which mode paging indicators are carried in data part of certain bursts having at least a data part and a training sequence part. According to an advantageous embodiment of the invention, the system comprises means 510 for adjusting the transmission level of at least the training sequence part of a burst carrying paging indicators to a certain level, said
 10 certain level having a predefined relation to the transmission level of the training sequence part of a burst belonging to a channel which is used in measurements of radio link quality. According to a further advantageous embodiment, said channel is the primary common control physical channel. According to an even further advantageous embodiment of the invention, said predefined relation is that the
 15 transmission level of at least the training sequence part of a burst carrying paging indicators is essentially the same as the transmission level of the training sequence part of a burst belonging to said channel.

Figure 6 illustrates a system according to an advantageous embodiment of the invention. Figure 6 shows a core network 101, a UTRAN (UMTS terrestrial radio
 20 access network) 102 and a mobile terminal (UE, user equipment) 103. The UTRAN is comprises a radio network subsystem 104. The RNS comprises a RNC (radio network controller) 105 and one or more node Bs 106. Each node B gives rise to at least one coverage area, i.e. cell, which is designated in Figure 6 by 107. According
 25 to an advantageous embodiment of the invention, the system comprises means 510 for adjusting the transmission level of at least the training sequence part of a burst carrying paging indicators to a certain level, said certain level having a predefined relation to the transmission level of the training sequence part of a burst belonging to a channel which is used in measurements of radio link quality. In this
 30 embodiment, the means 510 for adjusting the transmission level is located in the RNC. In other embodiments, the means 510 can be located in other network elements as well.

The invention has many advantages. For example, the invention allows better
 35 optimization of sleep mode operation for TDD terminals compared to the prior art. The invention also allows a reduction in the time required for reception of paging indicators and for measuring radio link quality. Further, the invention allows the determination of two different results from the reception of one burst in the sleep

mode, namely determination whether there is a paging message coming to the terminal or not from the PICH bits of the burst, and to determine the cell E_c/N_0 value for cell selection or reselection purposes from the received power level of the midamble of the same burst.

5

The invention can be applied in third generation cellular systems, such as the UMTS system.

10

In view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention. While a preferred embodiment of the invention has been described in detail, it should be apparent that many modifications and variations thereto are possible, all of which fall within the true spirit and scope of the invention.

15

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188